



Gempro2 Diamond Scale

Looking for the Ultimate Gem Scale? Look no further! Introducing the My Weigh GemPro 150 & 500. These scales includes all the functions, features, and accessories that jewelers have been searching for in ONE scale for years.

The GemPro is bound to surpass the expectations of even the most demanding jeweler. With dual-division capability, 3 calibration settings, 6 weighing modes, programmable auto-off, bright backlight, full tare feature, adjustable feet, level bubble, and an included AC adapter, this scale is in a league of its own. Also included is a calibration weight, a stainless steel weighing tray, an expansion scoop/bowl, and a protective hard carrying case.

My Weigh's GemPro has a capacity of up to 100 gram/500 carats with a division of either 0.001g/0.005ct or 0.002g/0.01ct.

This quality My Weigh digital scale is backed by a full Lifetime / 30-year international warranty.



- Three Calibration Modes (Pre-Calibration, Sensitivity Calibration, Linear Calibration)
- Retractable Wind Shield Cover
- Leveling System
- 6 Weighing Modes
- ASTM Class F2 Calibration Weight Included
- Runs on 4 AAA Batteries or AC Adapter (Included)
- SS Weighing Tray and Expansion Scoop/Bowl (Included)
- Full Tare Capabilities
- Programmable Auto Off (1-9 Minutes)
- Bright Backlight
- Adjustable Dual Division
- Protective Case (Included)
- Full Lifetime/30 Year International Warranty

GemPro-500	Specifications
Capacity (G500)	500.00ct 100g 3.5273oz 3.2150ozt 64.300dwt 1543.25gn
Readability	0.01ct 0.002g 0.0001oz 0.0001ozt 0.002dwt 0.05gn
Linearity	+/- 0.01ct 0.002g 0.0001oz 0.0001ozt 0.002dwt 0.05gn
Units (default)	g/ct/gn/oz/ozt/dwt
Calibration	Auto calibration with included calibration weight
Power Source	4 AAA batteries or AC Adapter (both included)
Tare range	Tare full capacity
Auto off (default)	adjustable
Operation temp.	10°C-30°C/50°F-86°F
Display	LCD 6 digitsx12mm
Dimensions	3.75" x 5.25" x 2.0"H
Warranty	Lifetime/30 year Worldwide Warranty

GemPro-150	Specifications
Capacity (G150)	150.00ct 30g 1.05820oz 0.96450ozt 19.290dwt 463.00gn
Readability	0.005ct 0.001g 0.00005oz 0.00005ozt 0.001dwt 0.02gn
Linearity	+/- 0.005ct 0.001g 0.00005oz 0.00005ozt 0.001dwt 0.02gn
Units (default)	g/ct/gn/oz/ozt/dwt
Calibration	Auto calibration with included calibration weight
Power Source	4 AAA batteries or AC Adapter (both included)
Tare range	Tare full capacity
Auto off (default)	adjustable
Operation temp.	10°C-30°C/50°F-86°F
Display	LCD 6 digitsx12mm
Dimensions	3.75" x 5.25" x 2.0"H
Warranty	Lifetime/30 year Worldwide Warranty